



## OPTIGUARD™ MCM4272 Boiler Layup Treatment

- Effective boiler layup for low-medium pressure boilers
- Easy to feed liquid formulation
- Simple, reliable control test
- Prevents boiler corrosion

### DESCRIPTION AND USE

OPTIGUARD™ MCM4272 is an advanced, multicomponent formulation specifically designed to prevent corrosion during boiler layup. OPTIGUARD MCM4272 contains molybdate to ensure passivation of ferrous metal surfaces and to prevent oxygen pitting. The molybdate also provides a reliable control test to ensure proper treatment levels are established.

### TREATMENT AND FEEDING REQUIREMENTS

Proper treatment levels for OPTIGUARD MCM4272 depend on many factors particular to a given boiler system. The product should be used in accordance with control procedures that GE Betz establishes for a specific application.

OPTIGUARD MCM4272 may be fed neat, or diluted to any convenient strength with softened makeup, condensate, or feedwater. The product may be fed directly to the boiler or added to the feedwater or condensate receiver tanks.

### PACKAGING INFORMATION

OPTIGUARD MCM4272 is a liquid blend, available in a variety of containers and delivery methods. Contact your GE Betz representative for details.

### STORAGE

Store OPTIGUARD MCM4272 at moderate temperatures and protect from freezing. If frozen, thaw completely and mix thoroughly prior to use.

### SAFETY PRECAUTIONS

A Material Safety Data Sheet containing detailed information about this product is available upon request.